

Portable Compressors

Mobilair™ M50

185 cfm @ 100 psig

NEW!



Tough, Dependable, and Quiet

The Mobilair™ M50 is a versatile portable screw compressor that offers heavy-duty performance in a light weight package. It is well suited for many applications including sand-blasting, pavement breaking, and general air tool use. These units are built to meet the demands of rental houses, repair trucks, and railroad applications.

Both the double-walled, rotomolded polyethylene canopy and the solid steel flooring protect the motor, airend, and critical components from dirt, water, and other contaminants. Rugged construction combined with extensive engineering

allow the M50 to retain its value year after year. The canopy is also designed to provide extremely low noise levels. Maximum sound level measured at 23 ft. is 76 db(A).

The M50 also features Kaeser's patent-pending anti-frost control feature. This thermostatically controlled valve automatically controls the compressed air temperature in relation to the current ambient temperature, which protects construction tools from freezing up, increases tool life, and extends compressor fluid life.

Standard Features:

- Direct drive rotary screw airend: Sigma profile produces more air with less fuel consumption
- Rotomolded polymer canopy is scratch and dent resistant
- 1 micron, 2-stage compressor inlet filter with maintenance indicator
- 10 micron engine air filter with maintenance indicator
- Exclusive anti-frost valve maintains optimum operating temperature and prevents tool freeze up
- Heavy duty, 4-cylinder Kubota diesel engine complies with Tier 4 emissions standards
- Tool box for convenient storage
- Highly efficient cooling system
- Modulation control
- Lighting package

Optional Features:

- Five year airend warranty
- Skid mount

Outstanding Advantages

- Contemporary, compact design
- Light weight, easily maneuverable
- One piece rotomolded canopy
- Easily accessible control panel
- Reflector and lighting package
- Torsion bar suspension
- Direct drive Sigma rotary screw airend
- Transparent fuel tank
- Thermstatically controlled combination valve
- Heavy duty inlet filter



Specifications

Compressor		Diesel Engine		Package		Dimensions (in.)	
Free air delivery	185 cfm	Make	Kubota V1505-T IDI	Fuel tank capacity	21 gal.	Length*	136½
Working Pressure	100 psig	Power at full load	41 hp	Weight, dry	1470 lb.	Width	56¾
		Full load speed	3000 rpm	Outlets	2 x 3/4"; 1 x 1	Height	55¾
		Off load running speed	2200 rpm	Sound level max	76 db(A) at 23 ft.	*includes tow bar	

Specifications are subject to change without notice.

KAESER COMPRESSORS

Built for a lifetime.™

www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Verendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

**Kaeser Compresores de México
S de RL de CV**
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

**Kaeser Compresores de
Guatemala y Cia. Ltda.**
Calz. Atanasio Tzul 21-00, zona 12
El Cortijo II, Bodega 501
01012-Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com

Certified Management Systems

